

FSI[®] DAT3060S MASS CASUALTY DECON SHOWER

ANSI/ISEA 113: American National Standard for Fixed & Portable Decontamination Shower Units • NFPA 1851 • OSHA 29 CFR 1910.120 (HAZWOPER)



DAT3060S

Dimensions (all approx.): 13' W × 20' L × 9' H (3.96 × 6.1 × 2.74 M) • 306 sq. ft. (outside-to-outside) • 335 lbs. (152 kg)

FSI's three-line Mass Casualty decontamination shower, 13' wide across three lanes (4', 5', 4' / 1.2, 1.5, 1.2 M). The DAT3060S runs three parallel lines through three or four sequential stages (undress, detergent shower #1, rinse shower #2, redress, or two personnel per lane at once) and processes 6 ambulatory or 3 non-ambulatory on stretchers, deploying in under 2 minutes. Four shower stages provide 20 total water discharge ports; an optional detergent injector routes stage #1 to detergent and stage #2 to rinse. The integral 13' × 12' floor holds up to 300 gal. (1200 L) behind a 6"/15 cm berm. Can be ordered in a modular configuration to allow attachment to a second FSI[®] DAT[®] Shower or Shelter.

SPECIFICATIONS

SPEC	VALUE
Configuration	3-line Mass Casualty (3 or 4 stage)
Footprint	13' × 20' × 9' H (3.96 × 6.1 × 2.74 M)
Floor area	306 sq. ft. (outside-to-outside)
Weight	335 lbs. (152 kg)
Carton	54" × 43" × 36" (136 × 108 × 91 cm)
Water capacity	Up to 300 gal. (1200 L), 6"/15 cm berm

SPEC	VALUE
Shower discharge	20 water discharge ports (4 stages)
Water inlets	Two ¾" (19 mm) GHT threaded
HVAC	8 × 19"/48 cm ducts
Interior	2 windows/side, 2 skylights, 3 man doors/end, dividers
Frame	Full-length roof berms + lateral supports
Compliance	ANSI/ISEA 113; NFPA 1851; OSHA 1910.120

INCLUDED • Electric inflator/deflator with hands free locking inflation adapter, high-pressure hose and valve with universal SCBA fitting, safety cord, integral ground floor, repair kit, manual, and carry bag. Velcro closure loops hang undress/redress kits on the inlet and outlet side. Meets known WHO, FEMA, DHS, and U.S. Military guidelines for CBRN decontamination.

CANOPY COLORS



Standard color is FSI Blue[®]. Green, White, Red, and Tan/Sand also available as standard. Other colors P.O.A.

INDEPENDENT PFAS TESTING: VERIFIED PFAS-FREE CANOPY

Independent laboratory testing by FITI Testing & Research Institute confirms the FSI Blue[®] outer canopy material contains no detectable per- and polyfluoroalkyl substances (PFAS). These results add to the canopy's existing REACH and OEKO-TEX STANDARD 100 compliance documentation.

Test methods	EN 17681-1:2025 • EN 14582:2016
Targeted PFAS (incl. PFOS, PFOA, PFNA, PFHxA)	Not detected (below 0.01 mg/kg detection limit)
Total fluorine screen	Not detected (below 30 mg/kg limit)



SCAN FOR FULL SPECS & QUOTE

DAT3060S AVAILABLE ACCESSORIES

Build the DAT3060S into a complete decon package. Order any item individually or as the DAT3060S-SYS / DAT3060S-SYS-LED bundle.



COMPLETE SYSTEM
DAT3060S-SYS



PROPANE WATER HEATER
F-ECC150WH
Propane tank not included



DETERGENT INJECTOR
FSI Heat 201



HAND SPRAYER TANK
F-HSP



LAY-FLAT HOSE
F-GH503510



BLADDER TANK, 150 GAL
F-HD150BT



WASTE PUMP
F-WSP33AA



ELEVATION GRID
F-TDMSPC



GROUND TARP, 10' × 10'
F-GS1



TUBE LIGHTING
F-1225-0500-STL



LED LIGHTING
F-SFLL-1M / F-SFLLPS-12V



HD EXTENSION CORD
F-EM-259A

Multiple optional accessories are available, including air and water heaters, air coolers, elevation grids, and waste-water pumps. For the full range and current pricing, visit www.fsinorth.com or contact FSI North America®.