

FSI[®] HEAT 200A PORTABLE WATER HEATER

Burner & Controls UL Listed to comply with ANSI/UL 296 • Certified to CAN/CSA B140.0 • Accepted by N.Y.C. M.E.A.



FSI-HEAT200A

Dimensions (all approx.): 47" H × 30" W × 39" D • 330 lbs (150 kg) • Shipping 44" W × 45" L × 48" H, 475 lbs (216 kg)

The FSI[®] HEAT 200A Multi-Fuel Water Heater is a heavy duty, wheeled cart unit: 440,000 BTU with a 14 GPM (56 LPM) total flow rate and multi-fuel capability. It includes a hot/cold water mixing valve with built-in anti-scald mechanism, three ¾" GHT water outlets with shutoff valves, an in-line analog temperature gauge, and a removable 9 gallon (34 L) fuel container. Maximum water temperature is 210°F (99°C). The HEAT 200A supplies hot water to FSI[®] hazmat decon showers as well as other makes and models.

SPECIFICATIONS

SPEC	VALUE
Output	440,000 BTU
Total flow rate	14 GPM (56 LPM)
Max temperature	210°F (99°C)
Power	115V / 1 Ph / 60 Hz, 15 amps
Alt. power	220V 50 Hz at no added charge; specify with order
Fuel	Diesel #1 or #2, JP4, JP8, Home Heating Oil, Kerosene

SPEC	VALUE
Fuel container	9 gal (34 L) plastic, removable
Water inlet	Single ¾" (19 mm) GHT
Water outlets	3 × ¾" GHT with shutoff valves
Mixing valve	Hot/cold with built-in anti-scald mechanism
Temperature gauge	In-line analog
Burn rate	Approx. 1.25 gal/hr; approx. 7.2 hours per tank



REAR VIEW

Outlet valves, temperature gauge, mixing valve, power box



WITH FSI HEAT 201

Detergent injector mounted



OUTLET MANIFOLD

Shutoff valves and mixing valve

OPTIONS • Booster pump offered P.O.A. • 10 ft fuel line extension to allow connection to an external fuel source, priced P.O.A. • 220V 50 Hz models available at no added charge; specify with order.

ACCESSORY: FSI HEAT 201 DETERGENT INJECTOR

Dema-style detergent injector with filter for use with the FSI Heat 200/200A or other water heaters. Induction rate 0.2–2%. Inline detergent dosing for decon shower and wash-down operations.



SCAN FOR FULL SPECS & QUOTE